




TRANSPONDERS



	PASSIVE LOOP USE				ACTIVE LOOP USE				
	WIRED ELITE	RECHARGEABLE ELITE	WIRED LS	RECHARGEABLE LS	RK	RF Radio 2,4 Ghz	RC	RT Waterproof	RF-S Radio 2,4 Ghz Waterproof
REFERENCE	TCTEF	TCTEB3	TCTLSF	TCTLSB3	TCTRK	TCTRF	TCTRC	TCTRT	TCTRF-S
WARRANTY	3 years	3 years	3 years	3 years	3 years	1 year (battery not guaranteed)	1 year (battery not guaranteed)	2 years (battery not guaranteed)	1 year
POWER SUPPLY	12V (2 wires)	Lithium Battery	12V (2 wires)	Lithium Battery	Lithium Battery	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2450 Lithium
AUTONOMY	Permanent supply	4 days	Permanent supply	5 days	5 years or 200 000 transit	3/4 years or 122 000 transit	3/4 years or 122 000 transit	3/4 years or 122 000 transit	3 years
CHARGE CYCLE	-	14 - 18h	-	14 - 18h	Non-replaceable Battery	Interchangeable Battery	Interchangeable Battery	Non-replaceable Battery	Non-replaceable Battery
MAX DETECTION HEIGHT	2,80 m / 9,2 ft	2,80 m / 9,2 ft	2,80 m / 9,2 ft	2,80 m / 9,2 ft	0,50 m / 1,64 ft	3 m / 9,9 ft	1,20 m / 3,93 ft	1,20 m / 3,93 ft	3 m / 9,9 ft
MAX SPEED DETECTION	360 km/h / 223,7 mph	360 km/h / 223,7 mph	200 km/h / 124,3 mph	200 km/h / 124,3 mph	120 km/h / 74,6 mph	140 km/h / 87 mph	120 km/h / 74,6 mph	120 km/h / 74,6 mph	140 km/h / 87 mph
DIMENSIONS	68 x 27 x 23 mm 2,7 x 1,1 x 0,9 inch	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 inch	68 x 27 x 23 mm 2,7 x 1,1 x 0,9 inch	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 inch	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 inch	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 inch	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 inch	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 inch	42 x 43 x 6 mm 1,6 x 1,7 x 0,2 inch
WEIGHT	80 g / 2,8 oz	80 g / 2,8 oz	80 g / 2,8 oz	80 g / 2,8 oz	80 g / 2,8 oz	19 g / 0,7 oz	19 g / 0,7 oz	19 g / 0,7 oz	11 g / 0,4 oz
TEMPERATURE RANGE	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F
SET	No need holder	Holder and Clip	No need holder	Holder and Clip	Holder and Clip	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap	Neopren Strap
SPORT	Cars Speed Bike Truck Karting	Cars Speed Bike Truck Karting	Motocross Supercross Kartcross Rallycross Follcar Karting	Motocross Supercross Kartcross Rallycross Follcar Karting	Rental Karting	Rental Karting Cycling Running Cross skiing Roller Skating Motocross	Rental Karting Cycling Running Cross skiing Roller Skating	Rental Karting Cycling Running Cross skiing Roller Skating Triathlon	Cycling Running Cross skiing Roller Skating Triathlon



40 TRANSPONDERS SUITCASE

Elite and LS rechargeable transponders are also sold with charging suitcase of maximum 40 transponders (the charger and the power supply are integrated to the suitcase).

INDIVIDUAL KITS / ELITE AND LS



Elite and LS rechargeable transponders are also sold in individual kit including 1 holder, 1 clip and 1 charger.

(LS model)

TAG HEUER BY CHRONELEC : EXPERIENCE AND TECHNOLOGY

The experience of TAG Heuer by Chronolec in timing, allowed the elaboration of a whole range of transponders.

Their reliable technology makes these transponders, **undeniable and essential precision tools**. Whatever the sport, the level of competition, the technical constraints, you will always find the right transponders for your needs.



23, rue du Comté de Montbéliard 25660 Montfaucon - FRANCE
 contact@itschrono.com +33 (0)3 81 57 52 09 www.itschrono.com



TAGHeuer
 PROFESSIONAL TIMING